



# Technical Data Sheet

Revision: March 15, 2025  
Supersedes: New  
Ref. #: Tool/Article

## Sealant Smoothing Tool

### DESCRIPTION

GE Sealant Smoothing Tool is reusable and designed for smoothing all types of sealants to achieve a perfect finish.

**Available as:**

Item #	Package	Color
3022728	Carded tool	Blue

### FEATURES & BENEFITS

- Easy to use
- Reusable
- Achieve a professional finished look

### RECOMMENDED FOR

Use with all types of sealants

### INSTRUCTIONS FOR USE

1. Apply a bead of sealant to the desired area taking care not to over apply.
2. Select desired profile on the Sealant Smoothing Tool.
3. Place the tool at the start of the sealant bead with the angled surface pointing towards the angle of travel.
4. Pressing down firmly, move the Sealant Smoothing Tool at a uniform rate to achieve the perfect finish.
5. Remove excess sealant from Sealant Smoothing Tool immediately after use with a dry cloth.

### DISCLAIMER

The information and recommendations contained herein are based on our research and are believed to be accurate, but no warranty, express or implied, is made or should be inferred. Henkel recommends purchasers/users should test the products to determine acceptable quality and suitability for the intended use. All adhesive/sealant applications should be tested under simulated or actual end use conditions to ensure the adhesive/sealant meets or exceeds all required project specifications. Since assembly conditions may be critical to adhesive/sealant performance, it is also recommended that testing be performed on specimens assembled under simulated or actual production conditions. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement, or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

### LIMITED WARRANTY

This product is warranted by Henkel Corporation to be free from defects in materials when used as directed. Henkel's sole obligation shall be, at its option, to replace or refund the purchase price of product proven to be defective. Henkel makes no other warranty – express or implied – including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE and will not be liable for consequential or incidental damages. This Limited Warranty gives you specific legal rights, which vary from state to state. For warranty assistance, contact Henkel at 1.877.607.7407 M-F 9:00 am to 4:00 pm ET.

GE is a registered trademark of General Electric Company and is used under trademark license by Henkel.

For Technical Assistance call : 1-877-607-7407 – Mon - Fri 9:00a – 4:00p ET

[www.gesealants.com](http://www.gesealants.com)



Founded in 1876, Henkel is a global leader in the consumer and industrial businesses. Henkel operates worldwide with leading brands and technologies in three business areas: Laundry & Home Care, Beauty Care and Adhesive Technologies.

Henkel Corporation - Professional & Consumer Adhesives Headquarters - Rocky Hill, CT 06067

[www.henkelna.com](http://www.henkelna.com)