



Technical Data Sheet

Revision: January 1, 2025
Supersedes: New
Ref. #: 252778

Interior Fill Acrylic Putty

DESCRIPTION

GE Interior Fill acrylic putty is ideal for use in small holes and cracks in drywall, wood, brick or concrete. This product dries quickly for fast repairs.

Available as:

Item #	Country	Package	Size	Color
3019891	USA	Squeeze tube	5.5 fl. oz. (162 mL)	White

FEATURES & BENEFITS

- Formulated for use on walls, trim, and baseboards
- Paintable
- 15-minute speed dry
- Easy to use

RECOMMENDED FOR

Interior Fill adheres to wood, plaster, drywall, wallboard, masonry, brick and concrete

LIMITATIONS

Should not be considered for:

- Exterior use
- Large and deep holes
- Underwater use or in applications where the product will be in contact with moisture or water
- Repairs subject to movement
- Hanging pictures

TECHNICAL DATA

Typical Uncured Physical Properties		Typical Application Properties	
<u>Color:</u>	White	<u>Application Temperature:</u>	Apply and cure above 40°F (5°C)
<u>Appearance:</u>	Liquid	<u>Drying Time:</u>	Approx. 15 minutes*
<u>Base:</u>	Polymer binder / natural limestone and other fillers	<u>Clean Up:</u>	Clean up uncured sealant residue immediately with warm, soapy water. Cut or scrape away cured sealant using a sharp-edged tool.
<u>Odor:</u>	Low, characteristic		
<u>VOC Content:</u>	< 1 %		
<u>Shelf Life:</u>	18 months from the date of manufacture (unopened)	<u>Lot Code Explanation:</u>	
		DDYY	
		DD = Last two digits of year of manufacture	
		YYY = Day of manufacture based on 365 days per year	
		Example: 22060 = March 1, 2022	

* For a thin crack with 1/16" – 1/8" (2 – 3 mm) depth/width. Drying time varies with application thickness, temperature and humidity.

Typical Cured Performance Properties

<u>Color:</u>	White	<u>Sandable:</u>	Yes
<u>Cured form:</u>	Hard solid	<u>Paintable:</u>	Yes
<u>Water Resistant:</u>	No		



Technical Data Sheet

Revision: January 1, 2025
Supersedes: New
Ref. #: 252778

DIRECTIONS

Tools Typically Required:

Putty knife, GE Cartridge and Tube Opener and Smoothing Tool; or utility knife.
Damp cloth or rag, 80 and 120 grit sandpaper.

Safety Precautions:

Wear gloves and wash hands after use.

Surface Preparation:

Surfaces must be clean, dry, structurally sound and free from dirt, dust, grease, oil, mildew, and other contaminants. Apply and allow to cure when product and surface temperatures are above 40°F (5°C).

Application:

- Knead tube well before using. Remove cap and trim tip to desired bead size using GE Cartridge and Tube Opener and Smoothing Tool.
- Squeeze filler into the opening and remove excess and smooth with a putty knife and/or damp cloth immediately after application. For best results, fill slightly above the surface level and overlap onto the surrounding area.

NOTE: For deeper cracks or holes, apply in 1/16" to 1/8" (2 mm to 3 mm) layers to avoid cracking due to shrinkage. Allow each layer to thoroughly dry before applying the next.

- Allow Interior Fill to dry for approximately 15 minutes for a 1/16" to 1/8" (2 mm to 3 mm) depth/width fill before sanding with 120 grit sandpaper. Remove sanding dust.
- Prime before painting. The patch can be painted with a water-based or oil-based paint.

NOTE: If Interior Fill is not completely dry, paint may bubble or lift.

Clean Up:

Clean hands and tools immediately with water. Cured filler may be sanded away.

STORAGE & DISPOSAL

DAMAGED BY FREEZING. Store tightly sealed in a cool, dry area away from heat and direct sunshine under standard conditions. Standard storage conditions are defined as 72 ± 4°F (22 ± 2°C) and < 50% relative humidity. Elevated temperatures or extreme cold temperatures will reduce shelf life. To dispose of unwanted product, squeeze out from tube, allow to harden and discard with trash.

LABEL PRECAUTIONS

DANGER! FLAMMABLE LIQUID AND VAPOR. VAPORS MAY CAUSE FLASH FIRE. HARMFUL IF SWALLOWED. EYE IRRITANT. Contains Isopropanol. May cause eye and skin irritation; avoid contact. Wash thoroughly after handling. Do not use or store near heat, sparks, or open flame. Do not smoke. Use only in a well-ventilated area. Avoid breathing vapors. **KEEP OUT OF REACH OF CHILDREN**

FIRST AID: For eye contact flush with water for 15 minutes. If symptoms develop and persist get medical attention. For skin contact, wash thoroughly with soap and water. If affected by inhalation, remove to fresh air and get medical attention if symptoms persist. If ingested, do not induce vomiting; call a physician or Poison Control Center immediately.



WARNING: Risk of cancer due to inhalation of silica quartz particles – www.P65Warnings.ca.gov

Refer to the Safety Data Sheet (SDS) for further information

DISCLAIMER

The information and recommendations contained herein are based on our research and are believed to be accurate, but no warranty, express or implied, is made or should be inferred. Henkel recommends purchasers/users should test the products to determine acceptable quality and suitability for the intended use. All adhesive/sealant applications should be tested under simulated or actual end use conditions to ensure the adhesive/sealant meets or exceeds all required project specifications. Since assembly conditions may be critical to adhesive/sealant performance, it is also recommended that testing be performed on specimens assembled under simulated or actual production conditions. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement, or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.



Technical Data Sheet

Revision: January 1, 2025
Supersedes: New
Ref. #: 252778

LIMITED WARRANTY

This product is warranted by Henkel Corporation to be free from defects in materials when used as directed. Henkel's sole obligation shall be, at its option, to replace or refund the purchase price of product proven to be defective. Henkel makes no other warranty – express or implied – including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE and will not be liable for consequential or incidental damages. This Limited Warranty gives you specific legal rights, which vary from state to state. For warranty assistance, contact Henkel at 1.877.607.7407 M-F 9:00 am to 4:00 pm ET.

GE is a registered trademark of General Electric Company and is used under trademark license by Henkel.

For Technical Assistance call : 1-877-607-7407 – Mon - Fri 9:00a – 4:00p ET
www.gesealants.com



Founded in 1876, Henkel is a global leader in the consumer and industrial businesses. Henkel operates worldwide with leading brands and technologies in three business areas: Laundry & Home Care, Beauty Care and Adhesive Technologies.

Henkel Corporation - Professional & Consumer Adhesives Headquarters - Rocky Hill, CT 06067
www.henkelna.com
